

8. Identified Hazards	9. Assess the Hazards: Initial Risk					10. Control Measures Developed for Identified Hazards: (Specific measures taken to reduce the probability of a hazard) Include all PPE	11. Assess the Hazards: Residual Risk					12. How to Implement the Controls: (May Be Filled in By Hand)	13. Supervisors and Evaluation by: (Continuous Leader Checks, Buddy System, etc.)
(Be Specific)	N	M	M	S	C	(Be Specific)	N	M	M	S	C	(Be Specific)	(Be Specific)
Improper Fueling: fire, explosion, spills, hazardous vapors.				X		-After running, stop and allow hot saws to cool for 1-5 minutes before refueling. Cool off period depends on air temp: hot weather=longer cool-off period. -Clear an area to bare ground for fueling the saw, if possible. -Otherwise, clear dead brush and grass away from fueling spot. -Do not smoke while fueling saw. -Fuel at least 10' from open flames.-Wipe spilled fuel off saw prior to re-starting. -Do not start saw within 10' of the fueling area. -Mix fuel and/or fuel saws in open areas, not in garages, storerooms, quarters,etc.	X					- Employees must receive training in chain saw operation prior to starting or using chain saws - Pre-project and pre-shift crew safety briefings - Refer to OSHA 29 CFR 1910.236 Logging Standards - Refer to BLM Manual 1112-2 Topic 12J	- Supervisor spot check - Crew leader continuous checks - Crew leader can ban any member from use of saw if, in his/her judgment, the crew member is an unsafe operator - Always team inexperienced operators with experienced members
Starting Saw; cuts from chain, sprains/strains from pulling starter rope				X		-Employees and volunteers must complete chainsaw operator's training prior to working with chainsaws. -Inspect saw for proper operating condition prior to the shift, and at least once more during the shift:: <ul style="list-style-type: none"> • Chain is properly tightened. • All handles and guards are in place and tight. • Chain brake is operational. • Muffler and spark arrester are in place. 	X					SAME AS ABOVE + Refer to saw operating manual.	SAME AS ABOVE + Supervisor crew chief will ensure that appropriate operators information specific to saw is available.
Cont Starting Saw, CONT'D						-Start the saw at or close to where you will be operating it to avoid traveling with a moving chain. -Do not start the saw if you aren't						SAME AS ABOVE	SAME AS ABOVE

